

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
1 February 2001 (01.02.2001)

PCT

(10) International Publication Number
WO 01/07818 A1

- (51) International Patent Classification⁷: **F16L 33/00**, 35/00, H02G 15/02
- (21) International Application Number: **PCT/DK00/00353**
- (22) International Filing Date: **30 June 2000 (30.06.2000)**
- (25) Filing Language: **Danish**
- (26) Publication Language: **English**
- (30) Priority Data:
PA 1999 01032 **23 July 1999 (23.07.1999)** **DK**
- (71) Applicant (*for all designated States except US*): **NKT FLEXIBLES I/S [DK/DK]**; Priorparken 510, DK-2605 Brøndby (DK).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **GLEJBØL, Kristian [DK/DK]**; Kvædehaven 109, DK-2600 Glostrup (DK).
- (74) Agent: **JAGTBOE, Ole**; NKT Research A/S, Priorparken 878, DK-2605 Brøndby (DK).
- (81) Designated States (*national*): AE, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *With international search report.*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **A METHOD OF SECURING REINFORCEMENT WIRES TO AN END TERMINATION OF A PIPELINE OR A CABLE, AN END TERMINATION, AND USES OF THE METHOD AND THE END TERMINATION**



(57) Abstract: In a method of securing tensile reinforcement elements (7) of a pipeline or a cable to an end termination (18), the end termination is provided with a plurality of locking holes through which the reinforcement elements to be secured are pulled. Insertion of a spreader element into the reinforcement element results in a local cross-sectional increase in the tensile reinforcement. The reinforcement element cannot move freely through the locking hole because of the local cross-sectional increase, thereby achieving mechanical locking.

BEST AVAILABLE COPY

WO 01/07818 A1